

## Family data sheet

# MAGNET SPOT SMALL

LED spot, easy installation with click magnet, magnetic rail Accessories and converter to be ordered separately, max. Track length 20m or 450W per feed



### CHARACTERISTIC

- Head can be swiveled 90° and rotated 355°
- Standard reflector 32° (on request also in 26° or 45° available)
- Voltage 24V DC (order converter separately)



## Product overview:

### Types:



black/ black




white/ black

### Light color:



2700K super warm white



3000K warm white

## Technical information:


### 2700K

<b>LED:</b>	CREE LED
<b>Total Watt:</b>	8W
<b>Reflector:</b>	32° (Standard)
<b>Net lumen:</b>	570lm
<b>Kelvin (CCT):</b>	2700K
<b>CRI:</b>	>90Ra
<b>Protection:</b>	IP20
<b>Protection class:</b>	3
<b>Life expectancy:</b>	L70/B10 = 50.000h
<b>Voltage:</b>	220~240V AC/ 48V DC
<b>Dimmability:</b>	DALI
<b>Converter:</b>	excluding external converter

### 3000K

<b>LED:</b>	CREE LED
<b>Total Watt:</b>	8W
<b>Reflector:</b>	32° (Standard)
<b>Net lumen:</b>	613lm
<b>Kelvin (CCT):</b>	3000K
<b>CRI:</b>	>90Ra
<b>Protection:</b>	IP20
<b>Protection class:</b>	3
<b>Life expectancy:</b>	L70/B10 = 50.000h
<b>Voltage:</b>	220~240V AC/ 48V DC
<b>Dimmability:</b>	DALI
<b>Converter:</b>	excluding external converter

## Drawings:



item number	watt	① kelvin	② reflector	③ color	control
LW48-MSS ① ② ③	8W	» 2700 « » 3000 «	» M « 32° (Standard)	» B « black/ black	DALI
		» 2700 «		» W « white/ black	

