Product family

SPOTY MINI

Recessed spotlight made of aluminum, available in different housing colors, with integrated LED insert 5W, swiveling, standard with 30 ° lens, CRI> 90Ra, incl. external converter (dimmable phase angle or phase endge), optional DALI / SwitchDim






CHARACTERISTIC


- made of aluminium
- rigid
- 3 housing colors to choose from
- with integrated LED insert 5W
- for ceiling cut-out Ø 68mm
- degree of protection: IP20
- external converter (dimmable phase angle or phase edge) optional DALI / SwitchDim



Product overview:

Housing color:







white

Light color:



2700K super warm white



3000K warm white

Control:





phase angle or phase edge dimmable



DALI dimmable (on request)

Drawings:





| Cut-Out: | Ø 68mm | | |
|-----------------|--------|--|--|
| Built-in depth: | 35mm | | |

Technical information:

| 5W Einsatz | | | | | | |
|------------------|-------------------------|-------|--|--|--|--|
| Total watt: | 5W | | | | | |
| Net umen: | 460lm | 512lm | | | | |
| Kelvin (CCT): | 2700K | 3000K | | | | |
| Protection: | IP20 | | | | | |
| CRI: | >90Ra | | | | | |
| Angle: | 30° | | | | | |
| Lebenserwartung: | 50.000h | | | | | |
| Voltage: | 100 ~ 230V AC/ 500mA DC | | | | | |

Article overview:

| item number | 0 watt | 2 kelvin | ⑤ lens | ₫ color | control |
|--|------------------|--------------------------|--|--|---------|
| LW25-RM- ① · ② · ⑤ · ② | »05 « | » 30 « 30° (Standard) | » B « black » S « brushed alu | dimmable phase angle or phase edge (Standard) | |
| | | | » W « white | DALI/SwitchDim (on request) | |

