



SPOTY ROUND 4



B schwarz



W weiß

Artikelnummer	Farbe	DALI PUSH	Leistung	Lichtfarbe	Lichtstrom	Primär	Sekundär	Winkel	CRI
LW25-R7-07-2700-1-	1	2	7W	2700K	840lm	220-240V	180mA	30°	CRI>90
LW25-R7-07-3000-1-	1	2	7W	3000K	879lm	220-240V	180mA	30°	CRI>90
LW25-R7-07-4000-1-	1	2	7W	4000K	905lm	220-240V	180mA	30°	CRI>90
LW25-R7-10-2700-1-	1	2	10W	2700K	1199lm	220-240V	250mA	30°	CRI>90
LW25-R7-10-3000-1-	1	2	10W	3000K	1255lm	220-240V	250mA	30°	CRI>90
LW25-R7-10-4000-1-	1	2	10W	4000K	1305lm	220-240V	250mA	30°	CRI>90
LW25-R7-11-WD-1-	1	2	10,8W	1800K - 3000K	885lm	220-240V	300mA	30°	CRI>90
LW25-R7-10-TW-1-	1	2	10,8W	2700K - 6500K	696lm - 1167 lm	220-240V	300mA	30°	CRI>90
LW25-R7-230-2700-	1	-	6W/230V	2700K	537lm	220-240V	230V	30°	CRI>90
LW25-R7-230-3000-	1	-	6W/230V	3000K	562lm	220-240V	230V	30°	CRI>90

- 1

B schwarz

W weiß
- 2

- TRIAC (Standard)

D DALI/PUSH



LED Einsatz SPOTY (Engine)
07 7W
10 10W



LED Einsatz SPOTY (Engine)
11 WD 10,8W WarmDIM
10 TW 10,8W Tunable White



LED Einsatz SPOTY (Engine)
230 6W/230V



PP250023B
Blendschutz



PP250021
Linse 15°
(für Engine 07/10/11WD/10TW)



PP250020
Linse 50°
(für Engine 07/10/11WD/10TW)



PP250015
Opal



PP250014
Wabenraster